

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>7</sup> :

B21J 15/32, B23P 19/00

A1

(11) International Publication Number:

WO 00/47350

(43) International Publication Date:

17 August 2000 (17.08.00)

(21) International Application Number: PCT/GB00/00472

(22) International Filing Date: 14 February 2000 (14.02.00)

(30) Priority Data:

9903148.6

12 February 1999 (12.02.99)

GB

(71) Applicant (for all designated States except US): HENROB LIMITED [GB/GB]; Aber Park, Flint, Flintshire CH6 5EX (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): COGLEY, Kevin [GB/GB]; 21 Norbury Avenue, Mossley Hill, Liverpool L18 1JQ (GB). BARFIELD, Philip, John [GB/GB]; 23 Shaftsbury Drive, Flint, Flintshire CH6 5EZ (GB).


(74) Agent: EVERY, David, Aidan; Marks &amp; Clerk, Sussex House, 83-85 Mosley Street, Manchester M2 3LG (GB).

(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

With international search report.

(54) Title: FASTENER DELIVERY APPARATUS



## (57) Abstract

A fastener delivery tube (1) is connected between a supply of fasteners, such as rivets (2), and the nose of a fastener setting machine. The delivery tube (1) is connected to an outlet tube (7) of a source of compressed air (3), the outlet tube (7) having an internal bore substantially equal in size to the internal bore of the delivery tube (1). The supply of fasteners is connected to the delivery tube via a feeder tube (9) and transfer gate (4). The transfer gate (4) is sealed so as to prevent leakage of air from the delivery tube (1). The arrangement reduces turbulence in the delivery tube (1) ensures that friction between the fastener (2) and the tube (1) is reduced and permits compressed air to be supplied at significantly lower pressure than has heretofore been possible.